

# METRO VANCOUVER

## METRO VANCOUVER REQUIREMENTS

The Metro Vancouver Food Sector Grease Interceptor Bylaw (No. 268, 2012) establishes maintenance requirements and limits on the amount of grease and solids that can flow out of grease interceptors and into sewers. Schier manufactures, tests, and certifies the Great Basin™ line of indoor and indoor/outdoor commercial grease interceptors to satisfy the requirements outlined in this bylaw, as well as in accordance with ASME A112.14.3 and CSA B481.

### GREASE INTERCEPTORS



**GB1**  
20 / 25 GPM  
70 / 64 lbs.  
capacity



**GB2**  
35 / 50 GPM  
130 / 127 lbs.  
capacity



**GB3**  
50 / 75 GPM  
272 / 175 lbs.  
capacity



**GB-50**  
50 / 75 GPM  
439 / 287  
capacity



**GB-75**  
75 GPM  
861 lbs. capacity



**GB-250**  
100 / 200 GPM  
1,895 / 1,196 lbs.  
capacity



**GB-500**  
100 GPM  
3,048 lbs.  
capacity



**GB-1000**  
100 / 200 GPM  
5,495 / 4,959 lbs.  
capacity



**GB-1500**  
100 / 200 GPM  
10,061 / 9,446 lbs.  
capacity



**GB-250-250HF**  
250 GPM  
1,068 lbs. capacity



**GB-500-250HF**  
250 GPM  
1,859 lbs. capacity



**GB-500-500HF**  
500 GPM  
1,000 lbs. capacity

Schier also manufactures the following factory-rated "high flow" (HF) units in accordance with the standards prescribed in the American Society of Plumbing Engineers Data Book, Volume 4, Chapter 8, Grease Interceptors.

All grease interceptors in this jurisdiction must be installed with an accessible sampling port downstream of the unit with the purpose of providing access for visual inspection and/or sampling.

### SEWER VIEWER™ WASTEWATER SAMPLING PORTS

**SV10**



**SV24**



**SV24-0**



### LOCALLY REPRESENTED BY



**HY-LINE SALES**

O: (604) 856-5648 | [hylinesales.com](http://hylinesales.com)



**SCHIER**

LIFETIME GUARANTEED **GREASE INTERCEPTORS**